



Product Guide

	MICRO X-II Series					XS Series			METAL SKIN Series		
Series											
Product	 Micro X-II	 Micro X-II Paintshop	 Micro X-II Autoclavable	 Micro X-II Plus Automotive	 Nano ^x II	 Dash-On XS	 Dot-On XS	 Dot Wedge	 Mercury Metal Skin	 Platinum Metal Skin	 Titanium Metal Skin
Operating frequency	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 865-868 MHz (EU)	860-960 MHz (Global)	902-928 MHz (US) 865-868 MHz (EU)	902-928 MHz (US) 865-868 MHz (EU)
IC type	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Qstar-56GN	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Impinj Monza 4E	Monza R6-P	Impinj Monza M5
Memory configuration	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	496-EPC bits; 2K-bit user memory; 256-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory,	48-bit serialized TID, 496 EPC bits, 128-bit user memory	32 bits user memory, 128 bits EPC, 96 bits TID	48-bit serialized TID, 128 EPC bits
Read range on metal (2W ERP)	Up to 33 ft (10 m)	Up to 33 ft (10 m)	Up to 33 ft (10 m)	Up to 23 ft (7 m)	Up to 20 ft (6 m)	Up to 6.6 ft (2 m)	Up to 5 ft (1.5 m)	Up to 3.3 ft (1 m)	Up to 16 ft (5 m)	Up to 13 ft (4 m)	Up to 4 ft (1.2 m)
Read range off metal	Limited	Limited	Limited	Limited	Limited	Limited	Limited	Limited	Up to 13 ft (4 m)	Up to 3.3 ft (1 m)	Up to 4 ft (1.2 m)
Case material	Engineering grade nylon polymer	Engineering grade nylon polymer	Engineering grade nylon polymer	Engineering grade nylon polymer	Engineering grade nylon polymer	Ceramic	Ceramic	High performance engineering polymer	Not applicable	Not applicable	Not applicable
Mounting system	Rivet hole, ø 0.12 in (3.2 mm); adhesive (optional)	Screws (Rivet hole, M3) Pop rivets (Max size 2.4mm)	Screws (Rivet hole, M3) Pop rivets (Max size 2.4mm)	Screws (Rivet hole, M4) Pop rivets (Max size 3.2mm) Adhesive bondings	High performance adhesive	Epoxy	Epoxy	Press fit	High performance adhesive	High performance adhesive	High performance adhesive
Operating temperature	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-22°F to +185°F (-30°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)
Application temperature	-40°F to +482°F (-40°C to +250°C)	-40°F to +482°F (-40°C to +250°C)	-40°F to +302°F (-40°C to +150°C)	-40°F to +482°F (-40°C to +250°C)	-40°F to +302°F (-40°C to +150°C)	-40°F to +302°F (-40°C to +150°C)	-40°F to +302°F (-40°C to +150°C)	-58°F to +428°F (-50°C to +220°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)
Compression strength	181 psi (1250 kPa)	181 psi (1250 kPa)	181 psi (1250 kPa)	725psi (5000 kPa)	166.8 psi (1150 kPa)	790 psi (5447kPa)	790 psi (5447kPa)	10,100psi (70 MPa)	92 psi (634 kPa)	14 psi (97 kPa)	58 psi (400 kPa)
IP classification	IP68	IP68	IP69K	IP68	IP68	IP68	IP68	IP68	Not applicable	IP68	Not applicable
Dimensions	2.01 x 1.43 x 0.30 in (51 x 36.3 x 7.5 mm)	2.01 x 1.43 x 0.30 in (51 x 36.3 x 7.5 mm)	2.01 x 1.43 x 0.30 in (51 x 36.3 x 7.5 mm)	2.27 x 1.43 x 0.30 in (57.6 x 36.2 x 7.5 mm)	1.25 x 0.51 x 0.20 in (31.7 x 12.8 x 4.8 mm)	0.48 x 0.12 x 0.09 in (12.3 x 3 x 2.2 mm)	ø 0.24 x 0.1 in (ø 6 x 2.5 mm)	ø 0.405 x 0.181 in ø 10.3 x 4.6mm	4 x 1.5 x 0.03 in (101.6 x 38 x 0.76 mm)	2.8 x 0.75 x 0.04 in (58.5 x 19 x 1.1 mm)	1.77 x 0.22 x 0.03 in (45 x 5.6 x 0.86 mm)
Weight	0.92 oz (26 g)	0.98 oz (28 g)	0.98 oz (28 g)	1.06 oz (30 g)	0.18 oz (5 g)	0.016 oz (0.44 g)	0.012 oz (0.34 g)	0.28 oz (8 g)	Reel: 4.85 lbs (2.2 kg)	Reel: 2.64 lbs (1.2 kg)	Reel: 2.54 lbs (1.15 kg)
Suggested applications	Bulk container tracking, vehicle tracking, post-paint oven baking, medical equipment tracking	Automotive manufacturing	Healthcare Equipments Management Assets Tracking in Autoclavable Environment	Automotive manufacturing	Tool tracking, WIP conveying equipment, IT/ telecom management, instrument tracking, weapons tracking	Instrument tracking, tool tracking, medical device management, source tagging	Instrument tracking, tool tracking, medical device management, source tagging	Onshore and Offshore Pipes Heavy Equipment and Tools Automotive Manufacturing Molds	Product authentication, IT asset tracking, global supply chain, cylinder tracking, foil-based packaging	Housewares, electronic equipment computer and laptops, cosmetics, foil-based packaging	Product authentication, IT asset and laptop tracking, radio and mobile equipment, foil-based packaging

Products marked with an asterisk(*) are available in autoclavable version.

Product Guide

Series	TRAK Series				TRAK OUTDOORS Series			PICO Series		ROSWELL Series	
Product	 Versa Trak	 Data Trak II	 Global Trak	 Slim Trak	 Container Trak	 Cargo Trak II	 Versa Trak II	 PicoX II Plus/Pico On Plus	 Pico-IN Plus	 Autoclavable Roswell/Roswell	 Xplorer
Operating frequency	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	860-960 MHz (Global)	860-960 MHz (Global)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)
IC type	Alien Higgs-3	Impinj Monza 4E	Impinj Monza 4QT	Alien Higgs-3	Impinj Monza R6-P	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3
Memory configuration	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	48-bit serialized TID, 496 EPC bits, 128-bit user memory	128-EPC bits; 512-bit user memory	96-bit EPC, 512-bit user memory, 64-bit TID	128 EPC bits, 32-bit user memory, 48-bit TID; Max user memory 64-bit, 48 TID, 96 EPC bits	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	96 EPC bits, extendable to 480 bits (512 bits user memory), 64-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID	96 EPC bits, extendable to 480-bit, 512-bit user memory, 64-bit TID
Read range on metal (2W ERP)	Up to 26 ft (8 m)	Up to 14.8 ft (4.5 m)	Up to 8 ft (2.5 m)	Up to 6.5 ft (2 m)	Up to 65 ft (20 m)	Up to 39 ft (12 m)	Up to 26 ft (8 m)	Up to 10 ft (3 m)	Up to 6.6 ft (2 m) when embedded	Up to 16.4 ft (5 m)	5 ft (1.5m) when embedded
Read range off metal (2W ERP)	Up to 13 ft (4 m)	Up to 8 ft (2.5 m)	Up to 6 ft (1.8 m)	Up to 4.9 ft (1.5 m)	Up to 39 ft (15 m)	Up to 20 ft (6 m)	Up to 13 ft (4 m)	Limited	Limited	Limited	Limited
Case material	Anti-UV Industry Grade Polymer	Polycarbonate	Polycarbonate	FR4	Anti-UV Industry Grade Polymer	Anti-UV Industry Grade Polymer	Anti-UV Industry Grade Polymer	Engineering grade nylon polymer/ Ceramic	Ceramic	Stainless steel/ Aluminum 6061-T6	Stainless steel
Mounting system	High performance adhesive/	Adhesive; built-in ø 0.1 in (2.6 mm) tethering hole	Adhesive; built-in ø 0.1 in (2.6 mm) tethering hole	Adhesive (TESA 51972), epoxy (optional)	Rivet hole, ø 1/4" M6, adhesive (optional) Cable tie, Metal Insert optional	Rivet hole, ø 0.14 in (3.5 mm); adhesive (optional)	Adhesive/Rivet hole, ø 0.14 in (3.5mm); adhesive (optional)	High performance adhesive	Epoxy, embedded	Welding, cable tie, rivet hole ø 0.19 in (ø 5 mm)	Press fit
Operating temperature	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to 185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-22°F to +185°F (-30°C to +85°C)	-22°F to +185°F (-30°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)
Application temperature	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +302°F (-40°C to +150°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +185°F (-40°C to +85°C)	-40°F to +302°F (-40°C to +150°C)	-40°F to +302°F (-40°C to +150°C)	-40°F to +482°F (-40°C to +250°C)	-58°F to +482°F (-50°C to +250°C)
Compression strength	26.1 psi (180 kPa)	14.5 psi (100 kPa)	14.5 psi (100 kPa)	106 psi (731 kPa)	29 psi (200 kPa)	29 psi (200 kPa)	26.1 psi (180 kPa)	174 psi (1200 kPa) / 170 psi (1176 kPa)	Packaging dependent	1145 psi (7900 kPa) / 115 psi (793 kPa)	30,000 psi (206 MPa)
IP classification	IP54	IP54	IP54	IP68	IP68	IP68	IP68	IP68	IP68	IP68	IP69K
Dimensions	1.98 x 0.67 x 0.21 in (50.3 x 17 x 5.3 mm)	1.50 x 0.51 x 0.16 in (38 x 13 x 4 mm)	1.50 x 0.51 x 0.16 in (38 x 13 x 4 mm)	2.22 x 0.234 x 0.051 in (56.5 x 5.95 x 1.3 mm)	5.46 x 4.99 x 0.47 in (138.8 x 126 x 12 mm)	3.94 x 1.02 x 0.35 in (100 x 26 x 8.9 mm)	2.88 x 0.9 x 0.33 in (73.3 x 22.8 x 8.3 mm)	0.70 x 0.43 x 0.2 in (17.7 x 10.9 x 5 mm) / 0.47 x 0.28 x 0.13 in (12 x 7 x 3.2 mm)	0.47 x 0.28 x 0.12 in (12 x 7 x 3 mm)	1.89 x 1.10 x 0.53 in (48 x 28 x 13.5 mm)	ø 1.11 x 0.33 in / (ø 28.3 x 8.5 mm)
Weight	0.39 oz (11 g) 0.11 oz (3 g)	0.08 oz (2.3 g)	0.09 oz (2.6 g)	0.035 oz (1 g)	1.45 oz (41 g)	0.62 oz (17.8 g) / 0.61 oz (17.2 g)	0.39 oz (11 g) / 0.11 oz (3 g)	0.07 oz (2 g) / 0.05 oz (1.4 g)	0.05 oz (1.4 g)	1.55 oz / 44 g 0.74 oz / 21 g	0.89 oz (25.4 g)
Suggested applications	Unit Load Device identification, logistics management, pallet tracking, RTI management, storage rack identification	IT asset management, Datacenter servers, Healthcare equipment	Global supply chain logistics, IT asset management, datacenter servers	IT server rack, military asset & weapon tracking, tool tracking	Outdoor using, Vehicle chassis and trailer tracking, Unit Load Device identification, logistics management	Outdoor using, Vehicle chassis and Unit Load Device identification, logistics management	Unit Load Device identification, logistics management, pallet tracking, RTI management, storage rack identification	Tool tracking, weapon tracking, medical device management, instrument tracking	IT and laptop tracking, tool tracking, embedded bolt identification, weapons tracking	Surgical Trays Oil & Gas Valve Wellhead Management Food Processing Plants, Automotive Manufacturing	Downhole and Surface Drill Pipes, Sub-sea Oil Pipes, BOPs and Wellheads

Products marked with an asterisk(*) are available in autoclavable version.